

Periodic Table of The Analytical Fittings

6-40 PORT THREAD	3750 PSI 1/16 M-644-03 / M-650 2-3 in-lbs Headless Micro Knurl PEEK	LEGEND	2500 PSI 1/8 P-331 / P-350 3-4 in-lbs Standard Knurl Tool Required? PEEK	TOOL N-290 3-4 in-lbs Micro Headless Knurl	ICONS Tool Required	NOTE Images are not to scale or shown at actual size.	For information, please visit www.biotechfluidics.com , or contact your local Biotech office: Europe: Biotech AB Phone: +46 300 569 180 info@biotechfluidics.com United States: Biotech USA LLC Phone: 612 703 5718 sales@biotechfluidics.com Japan: BioNik Inc. Phone: +81 545 389 125 info@bionikinc.com	25000 PSI 1/32 VHP-920 3 in-lbs 4 mm Hex SS / PEEK Blend	30000 PSI 1/32 VHP-900 / VHP-900-01 20 in-lbs 4 mm Hex SS	M4 PORT THREAD								
	15000 PSI 1/32 UH-904 3-4 in-lbs Headless Knurl PEEK Blend																	
6-32 PORT THREAD	3750 PSI 1/16 M-660 / M-650 2-3 in-lbs Headless Micro Knurl PEEK	4000 PSI .025 F-125 3-4 in-lbs Standard Micro Knurl PEEK	5000 PSI 360 µm F-124S 3-4 in-lbs Standard Micro Knurl PEEK	5000 PSI 1/32 F-126S 3-4 in-lbs Standard Micro Knurl PEEK	5000 PSI 1/32 F-126H 3-4 in-lbs Headless Micro Knurl PEEK	5000 PSI 360 µm F-124H 3-4 in-lbs Headless Micro Knurl PEEK	15000 PSI 1/32 PK-126 3-4 in-lbs Standard Micro Knurl PEEK Blend	15000 PSI 1/32 PK-126H 3-4 in-lbs Headless Micro Knurl PEEK Blend	15000 PSI 360 µm PK-124 3-4 in-lbs Standard Micro Knurl PEEK Blend	19000 PSI 1/32 MarvelX™ 2 in-lbs Knurl More info idex-hs.com	19000 PSI 1/32 MarvelXACT™ Torque Limiting Feature More info idex-hs.com	10-32 PORT THREAD						
10-32 PORT THREAD	4000 PSI 1/16 F-100 3-4 in-lbs Diamond Knurl PCTFE	5000 PSI 1/16 F-130 3-4 in-lbs Standard Knurl PEEK	5000 PSI 1/32 F-354 / LT-132 4 in-lbs Flush Nut SS / PEEK	5000 PSI 1/32 LT-110 / LT-132 4 in-lbs Standard Knurl PEEK	6000 PSI 190 µm F-200 / F-148 3-4 in-lbs Single Wing Delrin / PCTFE	6000 PSI 360 µm F-200 / F-151 3-4 in-lbs Single Wing Delrin / PCTFE	6000 PSI 1/32 F-200 / F-113 3-4 in-lbs Single Wing Delrin / PEEK	6000 PSI 1/16 F-200 / F-142 3-4 in-lbs Single Wing Delrin / PEEK	9000 PSI 1/16 F-195 / F-192 4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-198 / F-192 4 in-lbs Headless Knurl PEEK	9000 PSI 1/16 F-287 / F-192 4 in-lbs Standard Knurl PEEK / PEEK Blend		11000 PSI 1/16 VHP-3200 3-4 in-lbs Diamond Knurl SS / PEEK Blend	12000 PSI 1/16 PK-120BLK 8 in-lbs Standard Knurl PEEK Blend	20000 PSI 1/16 U-400 / U-401 20 in-lbs 1/4" Hex SS	20000 PSI 1/16 U-420 / U-401 20 in-lbs 1/4" Hex SS	25000 PSI 1/16 VHP-320 10 in-lbs 1/4" Hex SS / PEEK Blend	30000 PSI 1/16 VHP-200 / VHP-200-01 20 in-lbs 1/4" Hex SS
10-32 PORT THREAD	5000 PSI 1/16 F-120 3-4 in-lbs Standard Knurl PEEK	5000 PSI 1/16 F-130BLK 3-4 in-lbs Standard Knurl PEEK	5000 PSI 1/16 F-354 / LT-100 4 in-lbs Flush Nut SS / PEEK	5000 PSI 1/16 LT-110 / LT-100 4 in-lbs Standard Knurl PEEK	6000 PSI 190 µm F-300 / F-148 3-4 in-lbs Double Wing PEEK / PCTFE	6000 PSI 360 µm F-300 / F-151 3-4 in-lbs Double Wing PEEK / PCTFE	6000 PSI 1/32 F-300 / F-113 3-4 in-lbs Double Wing PEEK	6000 PSI 1/16 F-300 / F-142 3-4 in-lbs Double Wing PEEK	9000 PSI 1/16 F-196 / F-192 4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-350 / F-192 4 in-lbs Flush Nut SS / PEEK Blend	9000 PSI 1/16 F-284 / F-192 4 in-lbs Headless Knurl PEEK / PEEK Blend	10000 PSI 1/16 LT-110 / LT-135 7 in-lbs Standard Knurl PEEK / PEEK Blend	16500 PSI 1/32 PK-110 / PK-132 8 in-lbs Standard Knurl PEEK Blend	16500 PSI 1/16 PK-110 / PK-100 8 in-lbs Standard Knurl PEEK Blend	20000 PSI 1/16 U-320 / U-321 20 in-lbs 1/4" Hex SS	25000 PSI 1/16 VHP-325 10 in-lbs 1/4" Hex SS / PEEK Blend	30000 PSI 1/16 VHP-205 / VHP-200-01 20 in-lbs 1/4" Hex SS	
1/4-28 PORT THREAD	1000 PSI 1/16 P-249 2-3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-349 2-3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-331 / P-359 3-4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 F-356 / P-259 3-4 in-lbs Flush Nut SS / ETFE	1350 PSI 1/16 P-255 / P-259 3-4 in-lbs Standard Knurl PEEK / ETFE	1500 PSI 1/8 F-156 / P-360 3-4 in-lbs Female Knurl PEEK	1500 PSI 1/8 P-331 / P-360 3-4 in-lbs Standard Knurl PEEK	1500 PSI 1/8 F-356 / P-260 3-4 in-lbs Flush Nut SS / PEEK	1850 PSI 1/16 P-255 / P-260 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/32 F-356 / P-248 3-4 in-lbs Flush Nut SS / ETFE	2500 PSI 1/32 P-255 / P-248 3-4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/16 F-356 / P-250 3-4 in-lbs Flush Nut SS / PEEK	2500 PSI 1/16 P-255 / P-250 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 F-156 / P-350 3-4 in-lbs Female Knurl PEEK	2500 PSI 1/8 P-331 / P-350 3-4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 F-364 / LT-200 4 in-lbs Flush Nut SS / PEEK	20000 PSI 1/8 C-235 / C-236 40 in-lbs 3/16" Hex SS	
1/4-28 PORT THREAD	1000 PSI 1/8 P-100 3-4 in-lbs Diamond Knurl PCTFE	1000 PSI 1/8 F-364 / P-359 3-4 in-lbs Flush Nut SS / ETFE	1000 PSI 1/8 P-336 / P-359 3-4 in-lbs Headless Knurl PEEK / ETFE	1350 PSI 1/16 LT-115 / P-259 3-4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 P-287 / P-259 3-4 in-lbs Headless Knurl PPS / ETFE	1500 PSI 1/8 P-381 / P-360 3-4 in-lbs Standard Knurl PPS / PEEK	1500 PSI 1/8 F-364 / P-360 3-4 in-lbs Flush Nut SS / PEEK	1500 PSI 1/8 P-336 / P-360 3-4 in-lbs Headless Knurl PEEK	1850 PSI 1/16 LT-115 / P-260 3-4 in-lbs Standard Knurl PEEK	1850 PSI 1/16 P-287 / P-260 3-4 in-lbs Headless Knurl PPS / PEEK	2500 PSI 1/32 LT-115 / P-248 3-4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/32 P-287 / P-248 3-4 in-lbs Headless Knurl PPS / ETFE	2500 PSI 1/16 LT-115 / P-250 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/16 P-287 / P-250 3-4 in-lbs Headless Knurl PPS / PEEK	2500 PSI 1/8 F-364 / P-350 3-4 in-lbs Flush Nut SS / PEEK	2500 PSI 1/8 P-336 / P-350 3-4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 P-336 / P-350 3-4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 C-235 / LT-200 40 in-lbs 3/16" Hex SS / PEEK
1/4-28 PORT THREAD	1000 PSI 1/8 F-156 / P-359 3-4 in-lbs Female Knurl PEEK / ETFE	1000 PSI 1/8 LT-215 / P-359 3-4 in-lbs Standard Knurl PEEK / ETFE	1000 PSI 1/8 P-387 / P-359 3-4 in-lbs Standard Knurl PPS / ETFE	1350 PSI 1/16 P-232 / P-259 3-4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 P-420 / P-259 3-4 in-lbs Female Knurl PEEK / ETFE	1500 PSI 1/8 LT-215 / P-360 3-4 in-lbs Standard Knurl PEEK	1500 PSI 1/8 P-387 / P-360 3-4 in-lbs Headless Knurl PPS / PEEK	1850 PSI 1/16 P-232 / P-260 3-4 in-lbs Standard Knurl PEEK	1850 PSI 1/16 P-420 / P-260 3-4 in-lbs Female Knurl PEEK	2500 PSI 1/32 P-232 / P-248 3-4 in-lbs Headless Knurl PEEK / ETFE	2500 PSI 1/32 P-420 / P-248 3-4 in-lbs Female Knurl PEEK / ETFE	2500 PSI 1/16 P-232 / P-250 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/16 P-420 / P-250 3-4 in-lbs Female Knurl PEEK	2500 PSI 1/8 LT-215 / P-350 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 P-387 / P-350 3-4 in-lbs Standard Knurl PPS / PEEK	4500 PSI 1/8 LT-215 / LT-200 4 in-lbs Standard Knurl PEEK	4500 PSI 1/8 LT-210 / LT-200 4 in-lbs Double Wing PEEK	
1/4-28 PORT THREAD	1000 PSI 1/16 P-229 2-3 in-lbs Standard Knurl PEEK	1000 PSI 1/8 P-329 2-3 in-lbs Standard Knurl PEEK	1000 PSI 2.5 mm P-317 / P-366 3-4 in-lbs Standard Knurl PEEK	1350 PSI 1/16 P-213 / P-259 3-4 in-lbs Headless Knurl PEEK / ETFE	1350 PSI 1/16 P-219 / P-259 3-4 in-lbs Standard Knurl PEEK / ETFE	1350 PSI 1/16 P-217 / P-259 3-4 in-lbs Standard Knurl PEEK / ETFE	2500 PSI 1/32 P-213 / P-248 3-4 in-lbs Headless Knurl PEEK / ETFE	2500 PSI 1/32 P-219 / P-248 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/16 P-213 / P-250 3-4 in-lbs Headless Knurl PEEK	2500 PSI 1/8 P-219 / P-250 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 P-317 / P-352 3-4 in-lbs Standard Knurl PPS / PEEK	2500 PSI 1/8 P-319 / P-352 3-4 in-lbs Standard Knurl PEEK	2500 PSI 1/8 P-317 / P-355 3-4 in-lbs Standard Knurl PPS / PCTFE	2500 PSI 1.8 mm P-319 / P-355 3-4 in-lbs Standard Knurl PEEK / PCTFE	2500 PSI 1.8 mm P-357 / P-357-2 3-4 in-lbs Standard Knurl PEEK	5000 PSI 2.0 mm P-357 / P-357-2 3-4 in-lbs Standard Knurl PEEK	9000 PSI 1/16 F-197 / F-192 4 in-lbs Standard Knurl PEEK	20000 PSI 1/16 U-450 / U-401 20 in-lbs 3/16" Hex SS

HAND TIGHTENING/EXTENDER TOOLS							PRE-SET TORQUE TOOLS			
F-345 3-4 in-lbs Flush Nut-10-32	F-346 3-4 in-lbs Flush Nut 1/4-28	N-290 3-4 in-lbs Headless Knurl	P-277 3-4 in-lbs Standard Micro Knurl	P-297 3-4 in-lbs Headless Knurl	P-299 3-4 in-lbs Standard Knurl	P-399 3-4 in-lbs Micro Knurl	VHP-9000 2-10 in-lbs 4 mm Hex	VHP-1000 10 in-lbs 1/4" Hex	VHP-2000 14 in-lbs 1/4" Hex	P-1000 4 in-lbs Standard Knurl
ADJUSTABLE TORQUE DRIVER AND TORQUE DRIVER EXTENDER TOOLS										
VHP-4000 2-10 in-lbs 1/4" Drive	N-291 2-10 in-lbs Micro Headless Knurl	P-268 2-10 in-lbs 1/4" Hex	P-278 2-10 in-lbs Female Nut Knurl	P-279 2-10 in-lbs Micro Knurl	P-291 2-10 in-lbs Standard Knurl	P-292 2-10 in-lbs Headless Knurl				

